

This listing of changes to the specification paragraphs will replace all prior versions in the application:

Page 6, lines 20-26, change paragraph as follows:

Referring to Fig. 2, the card holder frame 20 can include plural moveable card frame holder(s) 30 such as an upper sign 90 and a lower sign 100. Fig. 2 shows the sign device 1 with an upper sign frame 90 and lower sign frame 100 extended out from the card holder frame 20. The detail showing how the moveable card frame holder(s) 30 are able to stay in an upward extended position and in a downward extended position will be described in reference to Figures 4-10A. The card frame holder 20 here uses three signboards 91, 42', 101 to spell out a message, which is depicted here as "GO TEAM! GO!."

Page 7, lines 8-13, change paragraph as follows:

Fig. 7 shows the sign device 1 of the preceding figures with the sign boards 42'', 44'' and plural top and bottom moveable card frame holders 30 separated there from. Front stationary card frame 50 can include right side, bottom side, and left side slot edges 52, 54, 56 for allowing the left, right, and bottom perimeter edges of the front sign board 42'' to slide into and out of. Likewise, rear stationary card frame 60 includes similar located slot edges(of which only 62 is shown) for allowing rear sign board 44'' to slide into and out of.

Page 7, lines 19-24, change paragraph as follows:

Fig. 9 is a side view of the sign device 1 of Fig. 8 with the top card frame 90 separated there from. Along inside of right side wall 22, and left side wall 26 of frame holder 20 can be narrow depth channel 130 having floor portion(s) 132. Fig. 9A is an enlarged view of the separated top card frame 90 and top of the sign device 1 of Fig. 9. The top card frame 90 has been slid out of the ~~longitudinal~~ inner side edge channels 140 within frame holder 20, and is ready to be positioned into a ~~narrow depth~~ inner side edge channel 130.